



COMPONENT	M.I. NO.
R1, 5-19, 22, 24-J, 16, 5, 59	330-302
R2, 67, 72, 73, 75, 73, 60-94, 115, 120	
R3, 37, 38, 21	330-402
R3	330-202
R4	330-60
R2C	330-50
R23, 35	330-202
R39-44, 54, 51	330-002
R45	330-302
R46	330-30
R47, 55, 43	330-102
R48, 52, 53, 40	330-302
R54	330-202
R56	330-302
R58	330-302
R61	330-222
R62, 69	330-302
R68	330-202
R70, 71	330-202
R74, 76, 95-97	330-402
R78, 79	330-202
R98-113	330-302
R116	330-202
R117-119	330-302
C1, 2, 40, 42, 50	300-402
C3, 19	300-202
C4, 7	300-190
C5, 11	300-190
C6	300-202
C8	300-302
C20-22	300-402
C10	300-190
C13, 16, C23-27, 51	300-190
C14	300-302
C15	300-110
C17	300-102
C18	300-130
C9	300-402
XTAL	321-0000
D1-31, 42-44, 46, 47	380-102
D32	380-210
D33, 34	380-200
D35, 36, 39, 40	380-400
D37	380-205
D41	380-206
D45	380-203
Q1	375-102A
Q2	375-102B
Q3	375-103B
TRANSIPAD (LS)	375-9000
HEATSINK (BIRCHTER)	375-9010
D46	380-210
D49, 50	380-000
R121	330-303
Q4	375-1000
C52	300-193

COMPONENT	WALL NO.
J1, 4-6	350-231
J2	654-118
J3	654-117
T.P. SRT LOW PROFILE	654-1157
16 PIN I.C. SOCKET	376-9012
24 PIN I.C. SOCKET	376-9053
25 PIN I.C. SOCKET	376-9006
22 PIN I.C. SOCKET	376-9010
14 PIN I.C. SOCKET	376-9012

DEC. 0.7 1978

[illegible]