THIS DOCUMENT IS THE PROPERTY OF WANG LABORATORIES, INC. AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS A BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION.

HOLE LEGEND

DRILLED OR PUNCHED HOLE TOLERANCES:	HOLE DIA.	TOL.
	.0135 to .125	±.002
	.126 to .350	±.003
	.351 to .500	±.004

IDENT	DESCRIPTION	QTY.
A		

LOCATION	W.L. PART NO	Trans. No. ±.2V	TTL No. of Vcc ±5VR
L1,3,11,21	376-0046	7	14
L2,5,9,10,15,18	-0104	6	16
L4	-0003	7	14
L5, L, 39	-0005	11	4
L6,7,12,22,23,33	-0002	7	14
L7, 19, 19, 23, 26, 34, 36	-0010	7	14
L20, 31	-0026	7	14
L14	-0031	7	14
L17, 28	-0126	1	8
L22	-0004	7	14
L24, 25, 34, 35	-0165	—	8
L32	-0008	8	16
L37, 38	-0055	7	14
L15	376-0025	7	14

PARTS LIST

COMPONENT	W.L. PART NO.
R1-7,9,20,24,27	330-3010
R8,10	-2047
R11,12,14,29,31,32,40,43,51	-3022
R13,17,18,21,22,25,28,33,35,37,39,42,44,46,49,50,52,60,62,63,64,65,66,67,68,69,83	-3047
R15,19,69	-4018
R16,55	-4056
R54	-4022
R24,36,38,41,59	-1010
R 30,47	-4010
R26,34	-4033
R45,61,72	-6015
R48	-4012
R56	330 -2033
R57	332 -1022
R58	330 -3033
R59	330-3012
C1,2	300-1010
C3	-4018
C4,6	-4010
C5,12	-4000
C10,27,42,43	-1904
C11	-4016
C9	-1910
C23	-1911
C13	-5005
C14,38,39,40	-4022
C15,16,19	-1901
C17,24,25	-2022
C18	-2010
C20,26	-4014
C21,22	-2110
C28-37	-1900
C7	300-1820
C31-34	360-1004
Q1,2	375-0017
Q3	375-1027
C41	300-4270
R67	330-3056
Q12	375-9004
Q3	375-9001
C44,45,46	360-1906
D23	300-7404

COMPONENT	W.L. PART No.
C43	300-1903
R23	330-4019
C8	300-4042

COMPONENT LAYOUT

CONN.1 — SIGNAL - TERMINAL DESIGNATIONS, VIEW FROM BOTTOM (WIRING) SIDE OF CONNECTOR

T.P.4	A 1		
+5VR	B 2	—	FT
±0V	C 3	—	CIP
DT1	D 4	—	DT4
DT2	E 5	—	DT5
DT3	F 6	—	DT6
IP	H 7	—	DT7
DT8	J 8	—	DSTB
T.P.3	K 9	—	T.R
CRI	L 10	—	BUSY
ACKLG	M 11	—	SLCT
SFG	N 12	—	POWER-ON PRIME
SPARE FUNCTION	P 13	—	FFP
VFP	R 14	—	LFP
SPARE FUNCTION	S 15	—	SPARE FUNCTION

CONN.2

EC	A 1	—	EC
CLR	B 2		
LFD	C 3	—	SPARE
LFE	D 4	—	SL
MAL FUNCTION	E 5		
CRE	F 6	—	XP
b7	H 7	—	PF
CF	J 8	—	TP6
COVER OPEN	K 9		
PAPER OUT	L 10	—	SFM
RS	M 11	—	SELECT SW.
ENDP	N 12	—	CRb
b5	P 13	—	b3
b4	R 14	—	b6
b2	S 15	—	b1

CONN.3

-12V	A	—	SLCTR
	K	—	T.P.5
FAULT	Q 3		
ALARM LIGHT	U 4	—	T.P.2
SPKR	E 5	—	CLRM
CLCR	F 6	—	PS
	H 7		
PAPER OUT	J 8	—	SELECT LIGHT
	K 9	—	OSCXT
PO	L 10	—	RD
RB	M 11	—	SELECT SW. OFF
TIME METER	N 12	—	T.R.
	P 13	—	±0V
	R 14	—	-5VR
FORM OVER-RIDE	S 15		

COMP. SIDE — WIRING SIDE

REVISION	BY	DATE
CHANGED PER ECN 4252		
ADDED C44		
CHANGED PER ECN 4302		
REVISED PER ECN 4355		
REVISED PER ECN 4355		
REVISED PER ECN 4355